


Z4.230

Specifications



Power at crankshaft	169.1 kW [230 hp]	Engine base	Toyota
Displacement	2.982 l [182 in ³]	Fuel system	Direct injection High pressure Common Rail Electronically controlled
Configuration	4 cylinders in line	Air intake	Turbocharged with intercooler
Operation type	4 stroke Diesel	Cooling	Closed with heat exchanger
Bore & stroke	96 x 103 mm [3.78 x 4.06 in]	Max mounting angle	0° Front up 0° Front down
Compression ratio	15:1	Alternator	12 Volt 100 Amp
Rated speed	3600 rpm	Rating	M6
Idling speed	700 rpm	Emission compliance	IMO Annex VI Compliant RCD2013/53/EU EPA marine Tier 3 BSO2
Peak torque	582.5 Nm		
Peak torque speed	2000 rpm		
Dry weight with Bravo X Three	476 kg [1049.4 lbs]		

Z4.230

169.1 kW [230 hp] at 3600 rpm

TECHNICAL DESCRIPTION

Engine block

- 4 cylinders in line
- 4 valves per cylinder
- Dual overhead camshaft (DOHC)
- Watercooled exhaust manifold
- Internal balancers

Fuel system

- Common Rail injection system
- Fuel filter with hand primer
- Integrated fuel cooler

Lubrication system

- Replacable full-flow oil filter
- Oil dipstick
- Transmission oil cooler

Cooling system

- Closed cooling with heat exchanger
- Gear driven self-priming raw water pump
- Coolant circulating pump
- Water cooled exhaust elbow

Electrical system & Instrumentation

- 12 V / 100 A alternator
- 12 V Electrical system
- Complete instrumentation including key switch and alarms
- Extension cable harness with plug-in connection

Air intake

- Dry turbocharger
- Intercooler

Other features

- Flexible engine mountings
- Transom (Trim system, Bull-horn & Mercathode)
- Trim indicator.

Optional equipments & accessories

- Throttle and shift controls
- Additional instrumentation & Fly bridge extension harness
- Water boiler systems
- Complete fuel systems
- Complete exhaust systems.

RATING

- Up to 500 annual operating hours
- Load factor up to 35%
- Fuel power for no more than 30 minutes out of each 8 hours of operation. The remaining operation time must be at or below cruising speed.


TRANSMISSIONS

Stern Drive


- Bravo X One
- Bravo X Three
- Bravo X Two
- Contact your local Nanni representative for more details and availability for transmission model and type.

PERFORMANCE CURVES


Power at crankshaft




Torque at crankshaft



Fuel consumption



DIMENSIONS WITH BRAVO X THREE



Nanni Industries S.A.S. France

11, Avenue Mariotte - Zone Industrielle
33260 La Teste - France
Tel: +33 (0)5 56 22 30 60
Fax: +33 (0)5 56 22 30 79

Nanni Trading S.R.L

Via Degli Olmetti, 5/B
00060 Formello (RM) - Italia
Tel: +39 06 30 88 42 51/52/53
Fax: +39 06 30 88 42 54

Technical data according to ISO 8665. Specifications are subject to change without notice. Images and illustrations may show non standard equipments. All combination of equipment & accessory are not available.

20172903A ENG